

830 Planning Schedule with Release Capability

Functional Group ID=**PS**

Introduction:

This Draft Standard for Trial Use contains the format and establishes the data contents of the Planning Schedule with Release Capability Transaction Set (830) for use within the context of an Electronic Data Interchange (EDI) environment. The transaction set can be used to provide for customary and established business practice relative to the transfer of forecasting/material release information between organizations. The planning schedule transaction may be used in various ways or in a combination of ways, such as: (1) a simple forecast; (2) a forecast with the buyer's authorization for the seller to commit to resources, such as labor or material; (3) a forecast that is also used as an order release mechanism, containing such elements as resource authorizations, period-to-date cumulative quantities, and specific ship/delivery patterns for requirements that have been represented in "buckets," such as weekly, monthly, or quarterly. The order release forecast may also contain all data related to purchase orders, as required, because the order release capability eliminates the need for discrete generation of purchase orders.

Notes:

- 1. Organizations use this transaction set to report war reserve material (WRM) requirements data to integrated material managers (IMMs)/inventory control points (ICPs).*
- 2. Use a single occurrence of this transaction set to transmit war reserve material requirements to one or more organizations. Use one occurrence of this transaction set to transmit a single or multiple transactions.*

Heading:

<u>Page No.</u>	<u>Pos. No.</u>	<u>Seg. ID</u>	<u>Name</u>	<u>Req. Des.</u>	<u>Max.Use</u>	<u>Loop Repeat</u>	<u>Notes and Comments</u>
5	010	ST	Transaction Set Header	M	1		
6	020	BFR	Beginning Segment for Planning Schedule	M	1		
Not Used	025	XPO	Preassigned Purchase Order Numbers	O	>1		
Not Used	040	CUR	Currency	O	1		
Not Used	050	REF	Reference Identification	O	12		
Not Used	060	PER	Administrative Communications Contact	O	3		
Not Used	070	TAX	Tax Reference	O	3		
Not Used	080	FOB	F.O.B. Related Instructions	O	1		
Not Used	090	CTP	Pricing Information	O	25		
Not Used	100	SAC	Service, Promotion, Allowance, or Charge Information	O	25		
Not Used	110	CSH	Sales Requirements	O	1		
Not Used	120	ITD	Terms of Sale/Deferred Terms of Sale	O	2		
Not Used	130	DTM	Date/Time Reference	O	10		
Not Used	140	PID	Product/Item Description	O	200		

830W - Planning Schedule with Release Capability (War Material Requirements)

Not Used	150	MEA	Measurements	O	40
Not Used	160	PWK	Paperwork	O	25
Not Used	170	PKG	Marking, Packaging, Loading	O	25
Not Used	180	TD1	Carrier Details (Quantity and Weight)	O	2
Not Used	190	TD5	Carrier Details (Routing Sequence/Transit Time)	O	12
Not Used	200	TD3	Carrier Details (Equipment)	O	12
Not Used	210	TD4	Carrier Details (Special Handling, or Hazardous Materials, or Both)	O	5
Not Used	220	MAN	Marks and Numbers	O	10
LOOP ID - N1					200
8	230	N1	Name	O	1
Not Used	240	N2	Additional Name Information	O	2
Not Used	250	N3	Address Information	O	2
Not Used	260	N4	Geographic Location	O	1
Not Used	270	REF	Reference Identification	O	12
Not Used	280	PER	Administrative Communications Contact	O	3
Not Used	290	FOB	F.O.B. Related Instructions	O	1
LOOP ID - LM					>1
Not Used	300	LM	Code Source Information	O	1
Not Used	310	LQ	Industry Code	M	100

Detail:

Page No.	Pos. No.	Seg. ID	Name	Req. Des.	Max.Use	Loop Repeat	Notes and Comments
LOOP ID - LIN							>1
10	010	LIN	Item Identification	M	1		
Not Used	020	UIT	Unit Detail	O	1		
14	021	DTM	Date/Time Reference	O	10		
Not Used	030	CUR	Currency	O	1		
Not Used	060	PO3	Additional Item Detail	O	25		
Not Used	070	CTP	Pricing Information	O	25		
Not Used	080	PID	Product/Item Description	O	1000		
Not Used	090	MEA	Measurements	O	40		
Not Used	100	PWK	Paperwork	O	25		
Not Used	110	PKG	Marking, Packaging, Loading	O	25		
Not Used	120	PO4	Item Physical Details	O	1		
Not Used	130	PRS	Part Release Status	O	1		
15	140	REF	Reference Identification	O	12		
Not Used	150	PER	Administrative Communications Contact	O	3		
Not Used	170	SAC	Service, Promotion, Allowance, or Charge Information	O	25		
Not Used	180	ITD	Terms of Sale/Deferred Terms of Sale	O	2		
Not Used	190	TAX	Tax Reference	O	3		
Not Used	200	FOB	F.O.B. Related Instructions	O	1		
Not Used	210	LDT	Lead Time	O	12		
Not Used	220	QTY	Quantity	O	>1		n1

830W - Planning Schedule with Release Capability (War Material Requirements)

Not Used	230	ATH	Resource Authorization	O	20	
Not Used	240	TD1	Carrier Details (Quantity and Weight)	O	1	
Not Used	250	TD5	Carrier Details (Routing Sequence/Transit Time)	O	12	
Not Used	260	TD3	Carrier Details (Equipment)	O	12	
Not Used	270	TD4	Carrier Details (Special Handling, or Hazardous Materials, or Both)	O	5	
Not Used	280	MAN	Marks and Numbers	O	10	
Not Used	290	DD	Demand Detail	O	10	
LOOP ID - SLN					100	
Not Used	300	SLN	Subline Item Detail	O	1	
Not Used	310	PID	Product/Item Description	O	1000	
Not Used	315	NM1	Individual or Organizational Name	O	10	
LOOP ID - N1					200	
17	320	N1	Name	O	1	
Not Used	330	N2	Additional Name Information	O	2	
Not Used	340	N3	Address Information	O	2	
Not Used	350	N4	Geographic Location	O	1	
Not Used	360	REF	Reference Identification	O	12	
Not Used	370	PER	Administrative Communications Contact	O	3	
Not Used	380	FOB	F.O.B. Related Instructions	O	1	
LOOP ID - LM					>1	
19	390	LM	Code Source Information	O	1	
20	400	LQ	Industry Code	M	100	
LOOP ID - FST					>1	
21	410	FST	Forecast Schedule	O	1	n2
Not Used	415	QTY	Quantity	O	>1	
23	420	SDQ	Destination Quantity	O	50	
LOOP ID - LM					>1	
25	430	LM	Code Source Information	O	1	
26	440	LQ	Industry Code	M	100	
LOOP ID - SDP					260	
Not Used	450	SDP	Ship/Delivery Pattern	O	1	
Not Used	460	FST	Forecast Schedule	O	260	
LOOP ID - SHP					25	
Not Used	470	SHP	Shipped/Received Information	O	1	
Not Used	480	REF	Reference Identification	O	5	

Summary:

Page No.	Pos. No.	Seg. ID	Name	Req. Des.	Max.Use	Loop Repeat	Notes and Comments
Not Used	010	CTT	Transaction Totals	O	1		n3
28	020	SE	Transaction Set Trailer	M	1		

Transaction Set Notes

1. QTY is used to specify supplemental quantities relevant to the forecast function. However, QTY is not related to the actual forecast quantity in the FST segments.
2. At least one occurrence of segment FST is required, either in the FST loop or within the SDP loop. These two loops are mutually exclusive.
3. Number of line items (CTT01) is the accumulation of the number of LIN segments. If used, hash total (CTT02) is the sum of the values of the quantities (FST01) for each FST segment.

Segment: **ST** Transaction Set Header
Position: 010
Loop:
Level: Heading
Usage: Mandatory
Max Use: 1
Purpose: To indicate the start of a transaction set and to assign a control number
Syntax Notes:
Semantic Notes: 1 The transaction set identifier (ST01) is used by the translation routines of the interchange partners to select the appropriate transaction set definition (e.g., 810 selects the Invoice Transaction Set).
Comments:

Data Element Summary

	<u>Ref.</u> <u>Des.</u>	<u>Data</u> <u>Element</u>	<u>Name</u>	<u>Attributes</u>
Must Use	ST01	143	Transaction Set Identifier Code	M ID 3/3
			Code uniquely identifying a Transaction Set	
			830 Planning Schedule with Release Capability	
Must Use	ST02	329	Transaction Set Control Number	M AN 4/9
			Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set	
			<i>A unique number assigned by the originator of the transaction set, or by the originator's application program.</i>	

Segment: **BFR** **Beginning Segment for Planning Schedule**

Position: 020

Loop:

Level: Heading

Usage: Mandatory

Max Use: 1

Purpose: To indicate the beginning of a planning schedule transaction set; whether a ship or delivery based forecast; and related forecast envelope dates

Syntax Notes: 1 At least one of BFR02 or BFR03 is required.

Semantic Notes: 1 If BFR01 contains the value "04" (Net Change), BFR09 is required.

2 BFR02 is the identifying number for a forecast assigned by the orderer/purchaser.

3 BFR06 is the forecast horizon start date: The date when the forecast horizon (envelope) begins.

4 BFR07 is the forecast horizon end date: The date when the forecast horizon (envelope) ends.

5 BFR08 is the date forecast generated: The date the forecast data was generated.

6 BFR09 is the date forecast updated: The date the forecast was updated with "net change" data. (Used only when data element 353 in BFR01 contains the value "04", meaning net change.)

Comments:

Data Element Summary

	<u>Ref.</u>	<u>Data</u>	<u>Name</u>	<u>Attributes</u>
	<u>Des.</u>	<u>Element</u>		
Must Use	BFR01	353	Transaction Set Purpose Code	M ID 2/2
			Code identifying purpose of transaction set	
		00	Original	
		77	Simulation Exercise	
			<i>Use to identify a simulated mobilization exercise transaction set. Activities initiating simulated mobilization exercises must ensure complete coordination with all activities involved. All transaction set recipients must use extreme caution to ensure that individual transactions do not process as action documents which affect accountable records.</i>	
Must Use	BFR02	127	Reference Identification	X AN 1/30
			Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier	
			<i>Use code "Z" for this data element to satisfy X12 syntax requirements.</i>	
Not Used	BFR03	328	Release Number	X AN 1/30
			Number identifying a release against a Purchase Order previously placed by the parties involved in the transaction	

Must Use	BFR04	675	Schedule Type Qualifier Code identifying the type of dates used when defining a shipping or delivery time in a schedule or forecast PR Planned Requirement Based <i>Use to indicate that requirements data reflect forecasted requirements.</i>	M ID 2/2
Must Use	BFR05	676	Schedule Quantity Qualifier Code identifying the type of quantities used when defining a schedule or forecast A Actual Discrete Quantities <i>Use to indicate that quantities reflect discrete requirements.</i>	M ID 1/1
Must Use	BFR06	373	Date Date expressed as CCYYMMDD <i>Must use to identify the forecast period start date.</i>	M DT 8/8
	BFR07	373	Date Date expressed as CCYYMMDD <i>Use to identify the forecast period end date.</i>	O DT 8/8
Must Use	BFR08	373	Date Date expressed as CCYYMMDD <i>Use to identify the transaction set preparation date. This date corresponds to the Universal Time Coordinate (UTC).</i>	M DT 8/8
Not Used	BFR09	373	Date Date expressed as CCYYMMDD	O DT 8/8
Not Used	BFR10	367	Contract Number Contract number	O AN 1/30
Not Used	BFR11	324	Purchase Order Number Identifying number for Purchase Order assigned by the orderer/purchaser	O AN 1/22
Must Use	BFR12	783	Planning Schedule Type Code Code identifying type of planning schedule used XF War Reserve Forecast <i>Must use to indicate the transaction is a war reserve material requirements forecast.</i>	O ID 2/2
Not Used	BFR13	306	Action Code Code indicating type of action	O ID 1/2

Segment:	N1 Name
Position:	230
Loop:	N1 Optional (Must Use)
Level:	Heading
Usage:	Optional (Must Use)
Max Use:	1
Purpose:	To identify a party by type of organization, name, and code
Syntax Notes:	<ol style="list-style-type: none"> 1 At least one of N102 or N103 is required. 2 If either N103 or N104 is present, then the other is required.
Semantic Notes:	
Comments:	<ol style="list-style-type: none"> 1 This segment, used alone, provides the most efficient method of providing organizational identification. To obtain this efficiency the "ID Code" (N104) must provide a key to the table maintained by the transaction processing party. 2 N105 and N106 further define the type of entity in N101.
Notes:	<i>Must use this 1/N1/230 loop to identify the organization originating the transaction set.</i>

Data Element Summary

	Ref.	Data	Attributes
	Des.	Element Name	
Must Use	N101	98 Entity Identifier Code	M ID 2/3
		Code identifying an organizational entity, a physical location, property or an individual	
		41 Submitter	
		Entity transmitting transaction set	
		<i>Must use to identify the organization submitting war reserve material (WRM) requirements data.</i>	
Not Used	N102	93 Name	X AN 1/60
		Free-form name	
Must Use	N103	66 Identification Code Qualifier	X ID 1/2
		Code designating the system/method of code structure used for Identification Code (67)	
		1 D-U-N-S Number, Dun & Bradstreet	
		9 D-U-N-S+4, D-U-N-S Number with Four Character Suffix	
		10 Department of Defense Activity Address Code (DODAAC)	
		M4 Department of Defense Routing Identifier Code (RIC)	
		An integral and predetermined participant in an established logistical system performing general logistic control, distribution, and storage functions	
Must Use	N104	67 Identification Code	X AN 2/80
		Code identifying a party or other code	

Not Used	N105	706	Entity Relationship Code Code describing entity relationship	O ID 2/2
Must Use	N106	98	Entity Identifier Code Code identifying an organizational entity, a physical location, property or an individual	O ID 2/3

FR

Message From

Must use to indicate the organization cited in N104 is originating the transaction.

Segment:	LIN Item Identification
Position:	010
Loop:	LIN Mandatory
Level:	Detail
Usage:	Mandatory
Max Use:	1
Purpose:	To specify basic item identification data
Syntax Notes:	<ol style="list-style-type: none"> 1 If either LIN04 or LIN05 is present, then the other is required. 2 If either LIN06 or LIN07 is present, then the other is required. 3 If either LIN08 or LIN09 is present, then the other is required. 4 If either LIN10 or LIN11 is present, then the other is required. 5 If either LIN12 or LIN13 is present, then the other is required. 6 If either LIN14 or LIN15 is present, then the other is required. 7 If either LIN16 or LIN17 is present, then the other is required. 8 If either LIN18 or LIN19 is present, then the other is required. 9 If either LIN20 or LIN21 is present, then the other is required. 10 If either LIN22 or LIN23 is present, then the other is required. 11 If either LIN24 or LIN25 is present, then the other is required. 12 If either LIN26 or LIN27 is present, then the other is required. 13 If either LIN28 or LIN29 is present, then the other is required. 14 If either LIN30 or LIN31 is present, then the other is required.
Semantic Notes:	1 LIN01 is the line item identification
Comments:	<ol style="list-style-type: none"> 1 See the Data Dictionary for a complete list of IDs. 2 LIN02 through LIN31 provide for fifteen different product/service IDs for each item. For example: Case, Color, Drawing No., U.P.C. No., ISBN No., Model No., or SKU.
Notes:	<p>1. Must use the 2/LIN/010 loop to identify the type of WRM and information related to the requirement forecast.</p> <p>2. Detailed WRM data identifies incremental monthly forecast quantities for a single line item stratified by type of WRM or by type of WRM and project code.</p> <p>3. When stratifying only by type of WRM (for other than Pre-Positioned War Reserve (PWR) requirements), use a single iteration of the 2/LM/390 loop to identify a single War Reserve Material Requirement Code and use multiple iterations of the 2/FST/410 loop to identify incremental monthly forecast quantities. Do not use the 2/LM/430 loop. This stratification method requires multiple iterations of the 2/LIN/010 loop for a single line item to identify each type of WRM.</p> <p>4. When stratifying by type of WRM and project code (for other than PWR requirements), use a single iteration of the 2/LM/390 loop to identify a single War Reserve Material Requirement Code; use multiple iterations of the 2/FST/410 loop to identify incremental monthly forecast quantities; and use a single iteration of the 2/LM/430 loop for each iteration of the 2/FST/410 loop to identify the project code associated with the quantity. This stratification method requires multiple iterations of the 2/LIN/010 loop for a single line item to identify</p>

each type of WRM.

5. For PWR forecast requirements, do not use the 2/LM/390 loop to identify the War Reserve Material Requirement Code. Instead, use two iterations of the 2/FST/410 loop to identify applicable incremental monthly forecast quantities; and use a single iteration of the 2/LM/430 loop, for each iteration of the 2/FST/410 loop, to identify the War Reserve Material Requirement Code and/or project code associated with the quantity.

Data Element Summary

	Ref. Des.	Data Element	Name	Attributes
Not Used	LIN01	350	Assigned Identification Alphanumeric characters assigned for differentiation within a transaction set	O AN 1/20
Must Use	LIN02	235	Product/Service ID Qualifier Code identifying the type/source of the descriptive number used in Product/Service ID (234) 1. Use only one of codes A1, A2, A4, FB, FS, MG, or YP to identify the material. Must use National Stock Number (NSN) when known. 2. When citing a manufacturer's part number (code MG), always use code ZB to identify the manufacturer's commercial and government entity (CAGE) code.	M ID 2/2
		A1	Plant Equipment Number Item identifier is a plant equipment number Use to identify plant equipment.	
		A2	Department of Defense Identification Code (DoDIC) Qualifies a code that uniquely identifies a type of explosive or ammunition Use to identify ammunition items.	
		A4	Subsistence Identification Number Item identifier is a brand-name resale subsistence item Use to identify subsistence items.	
		FB	Form Number Use to identify the form stock number.	
		FS	National Stock Number Must use the NSN when known.	
		MG	Manufacturer's Part Number Use to identify nonstandard material.	
		YP	Publication Number Use to identify the publication stock number.	

Must Use	LIN03	234	Product/Service ID Identifying number for a product or service	M	AN 1/48
	LIN04	235	Product/Service ID Qualifier Code identifying the type/source of the descriptive number used in Product/Service ID (234) ZB Commercial and Government Entity (CAGE) Code A code that identifies a commercial contractor authorized to do business with the U.S. government <i>Use with LIN02 code MG to uniquely identify a manufacturer's part number.</i>	X	ID 2/2
	LIN05	234	Product/Service ID Identifying number for a product or service	X	AN 1/48
Not Used	LIN06	235	Product/Service ID Qualifier Code identifying the type/source of the descriptive number used in Product/Service ID (234)	X	ID 2/2
Not Used	LIN07	234	Product/Service ID Identifying number for a product or service	X	AN 1/48
Not Used	LIN08	235	Product/Service ID Qualifier Code identifying the type/source of the descriptive number used in Product/Service ID (234)	X	ID 2/2
Not Used	LIN09	234	Product/Service ID Identifying number for a product or service	X	AN 1/48
Not Used	LIN10	235	Product/Service ID Qualifier Code identifying the type/source of the descriptive number used in Product/Service ID (234)	X	ID 2/2
Not Used	LIN11	234	Product/Service ID Identifying number for a product or service	X	AN 1/48
Not Used	LIN12	235	Product/Service ID Qualifier Code identifying the type/source of the descriptive number used in Product/Service ID (234)	X	ID 2/2
Not Used	LIN13	234	Product/Service ID Identifying number for a product or service	X	AN 1/48
Not Used	LIN14	235	Product/Service ID Qualifier Code identifying the type/source of the descriptive number used in Product/Service ID (234)	X	ID 2/2
Not Used	LIN15	234	Product/Service ID Identifying number for a product or service	X	AN 1/48
Not Used	LIN16	235	Product/Service ID Qualifier Code identifying the type/source of the descriptive number used in Product/Service ID (234)	X	ID 2/2
Not Used	LIN17	234	Product/Service ID Identifying number for a product or service	X	AN 1/48

Not Used	LIN18	235	Product/Service ID Qualifier Code identifying the type/source of the descriptive number used in Product/Service ID (234)	X	ID 2/2
Not Used	LIN19	234	Product/Service ID Identifying number for a product or service	X	AN 1/48
Not Used	LIN20	235	Product/Service ID Qualifier Code identifying the type/source of the descriptive number used in Product/Service ID (234)	X	ID 2/2
Not Used	LIN21	234	Product/Service ID Identifying number for a product or service	X	AN 1/48
Not Used	LIN22	235	Product/Service ID Qualifier Code identifying the type/source of the descriptive number used in Product/Service ID (234)	X	ID 2/2
Not Used	LIN23	234	Product/Service ID Identifying number for a product or service	X	AN 1/48
Not Used	LIN24	235	Product/Service ID Qualifier Code identifying the type/source of the descriptive number used in Product/Service ID (234)	X	ID 2/2
Not Used	LIN25	234	Product/Service ID Identifying number for a product or service	X	AN 1/48
Not Used	LIN26	235	Product/Service ID Qualifier Code identifying the type/source of the descriptive number used in Product/Service ID (234)	X	ID 2/2
Not Used	LIN27	234	Product/Service ID Identifying number for a product or service	X	AN 1/48
Not Used	LIN28	235	Product/Service ID Qualifier Code identifying the type/source of the descriptive number used in Product/Service ID (234)	X	ID 2/2
Not Used	LIN29	234	Product/Service ID Identifying number for a product or service	X	AN 1/48
Not Used	LIN30	235	Product/Service ID Qualifier Code identifying the type/source of the descriptive number used in Product/Service ID (234)	X	ID 2/2
Not Used	LIN31	234	Product/Service ID Identifying number for a product or service	X	AN 1/48

Segment: **DTM** **Date/Time Reference**

Position: 021

Loop: LIN Mandatory

Level: Detail

Usage: Optional (Must Use)

Max Use: 10

Purpose: To specify pertinent dates and times

Syntax Notes:

- 1 At least one of DTM02 DTM03 or DTM05 is required.
- 2 If DTM04 is present, then DTM03 is required.
- 3 If either DTM05 or DTM06 is present, then the other is required.

Semantic Notes:

Comments:

Notes: *Must use to identify the date of transaction preparation.*

Data Element Summary

	<u>Ref.</u>	<u>Data</u>	<u>Element</u>	<u>Name</u>	<u>Attributes</u>
Must Use	DTM01	374	Date/Time Qualifier		M ID 3/3
				Code specifying type of date or time, or both date and time	
				097 Transaction Creation	
				<i>Use to identify the date of transaction preparation.</i>	
Must Use	DTM02	373	Date		X DT 8/8
				Date expressed as CCYYMMDD	
Not Used	DTM03	337	Time		X TM 4/8
				Time expressed in 24-hour clock time as follows: HHMM, or HHMMSS, or HHMMSSD, or HHMMSSDD, where H = hours (00-23), M = minutes (00-59), S = integer seconds (00-59) and DD = decimal seconds; decimal seconds are expressed as follows: D = tenths (0-9) and DD = hundredths (00-99)	
Not Used	DTM04	623	Time Code		O ID 2/2
				Code identifying the time. In accordance with International Standards Organization standard 8601, time can be specified by a + or - and an indication in hours in relation to Universal Time Coordinate (UTC) time; since + is a restricted character, + and - are substituted by P and M in the codes that follow	
Not Used	DTM05	1250	Date Time Period Format Qualifier		X ID 2/3
				Code indicating the date format, time format, or date and time format	
Not Used	DTM06	1251	Date Time Period		X AN 1/35
				Expression of a date, a time, or range of dates, times or dates and times	

Segment:	REF Reference Identification
Position:	140
Loop:	LIN Mandatory
Level:	Detail
Usage:	Optional
Max Use:	12
Purpose:	To specify identifying information
Syntax Notes:	<ol style="list-style-type: none"> 1 At least one of REF02 or REF03 is required. 2 If either C04003 or C04004 is present, then the other is required. 3 If either C04005 or C04006 is present, then the other is required.
Semantic Notes:	1 REF04 contains data relating to the value cited in REF02.
Comments:	

Data Element Summary				
	<u>Ref.</u> <u>Des.</u>	<u>Data</u> <u>Element</u>	<u>Name</u>	<u>Attributes</u>
Must Use	REF01	128	Reference Identification Qualifier Code qualifying the Reference Identification TN Transaction Reference Number <i>Use to identify the transaction number.</i>	M ID 2/3
Must Use	REF02	127	Reference Identification Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier	X AN 1/30
Not Used	REF03	352	Description A free-form description to clarify the related data elements and their content	X AN 1/80
Not Used	REF04	C040	Reference Identifier To identify one or more reference numbers or identification numbers as specified by the Reference Qualifier	O
Not Used	C04001	128	Reference Identification Qualifier Code qualifying the Reference Identification	M ID 2/3
Not Used	C04002	127	Reference Identification Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier	M AN 1/30
Not Used	C04003	128	Reference Identification Qualifier Code qualifying the Reference Identification	X ID 2/3
Not Used	C04004	127	Reference Identification Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier	X AN 1/30
Not Used	C04005	128	Reference Identification Qualifier Code qualifying the Reference Identification	X ID 2/3
Not Used	C04006	127	Reference Identification	X AN 1/30

Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier

Segment:	N1 Name
Position:	320
Loop:	N1 Optional (Must Use)
Level:	Detail
Usage:	Optional (Must Use)
Max Use:	1
Purpose:	To identify a party by type of organization, name, and code
Syntax Notes:	<ol style="list-style-type: none"> 1 At least one of N102 or N103 is required. 2 If either N103 or N104 is present, then the other is required.
Semantic Notes:	
Comments:	<ol style="list-style-type: none"> 1 This segment, used alone, provides the most efficient method of providing organizational identification. To obtain this efficiency the "ID Code" (N104) must provide a key to the table maintained by the transaction processing party. 2 N105 and N106 further define the type of entity in N101.
Notes:	<ol style="list-style-type: none"> 1. <i>Must use one iteration of this 2/N1/320 loop to identify the organization to receive the transaction.</i> 2. <i>Use additional iterations to identify other organizations associated with the transaction.</i>

Data Element Summary

	<u>Ref.</u>	<u>Data</u>	<u>Element</u>	<u>Name</u>	<u>Attributes</u>
Must Use	N101	98		Entity Identifier Code	M ID 2/3
				Code identifying an organizational entity, a physical location, property or an individual	
			KA	Item Manager	
				The address of the person responsible for the management of an item of supply	
				<i>Must use to indicate the IMM/ICP.</i>	
			ZD	Party to Receive Reports	
				The organization designated to receive reports	
				<i>Use to indicate the organization(s) to receive reports.</i>	
Not Used	N102	93		Name	X AN 1/60
				Free-form name	
Must Use	N103	66		Identification Code Qualifier	X ID 1/2
				Code designating the system/method of code structure used for Identification Code (67)	
			1	D-U-N-S Number, Dun & Bradstreet	
			9	D-U-N-S+4, D-U-N-S Number with Four Character Suffix	
			10	Department of Defense Activity Address Code (DODAAC)	

			M4	Department of Defense Routing Identifier Code (RIC) An integral and predetermined participant in an established logistical system performing general logistic control, distribution, and storage functions	
Must Use	N104	67	Identification Code		X AN 2/80
			Code identifying a party or other code		
Not Used	N105	706	Entity Relationship Code		O ID 2/2
			Code describing entity relationship		
	N106	98	Entity Identifier Code		O ID 2/3
			Code identifying an organizational entity, a physical location, property or an individual		
			TO	Message To	
				<i>Must use with 2/N101/320 code KA to indicate the organization cited in N104 is receiving the transaction.</i>	

Segment:	LM Code Source Information
Position:	390
Loop:	LM Optional (Must Use)
Level:	Detail
Usage:	Optional (Must Use)
Max Use:	1
Purpose:	To transmit standard code list identification information
Syntax Notes:	
Semantic Notes:	
Comments:	1 LM02 identifies the applicable industry code list source information.
Notes:	<p><i>1. Use the 2/LM/390 loop to identify coded information maintained in department or agency documentation.</i></p> <p><i>2. Use the 2/LM/390 loop to stratify forecasts for other than PWR requirements by type of War Reserve Material Requirements Code. Cite the associated quantities in one or more iterations of the 2/FST/410 loop.</i></p> <p><i>3. Do not use to identify the War Reserve Material Requirement Code for PWR requirements.</i></p>

Data Element Summary

	Ref.	Data	Attributes
	Des.	Element Name	
Must Use	LM01	559 Agency Qualifier Code	M ID 2/2
		Code identifying the agency assigning the code values	
		DF Department of Defense (DoD)	
Not Used	LM02	822 Source Subqualifier	O AN 1/15
		A reference that indicates the table or text maintained by the Source Qualifier	

Segment: **LQ** Industry Code
Position: 400
Loop: LM Optional (Must Use)
Level: Detail
Usage: Mandatory
Max Use: 100
Purpose: Code to transmit standard industry codes
Syntax Notes: 1 If LQ01 is present, then LQ02 is required.
Semantic Notes:
Comments:
Notes: *Use to identify codes, as appropriate, consistent with management information requirements.*

Data Element Summary

Ref.	Data	Name	Attributes
<u>Des.</u>	<u>Element</u>	<u>Name</u>	<u>Attributes</u>
Must Use	LQ01	1270 Code List Qualifier Code	O ID 1/3
		Code identifying a specific industry code list	
		0 Document Identification Code	
		Codes that subclassify a transaction	
		LZ War Reserve Material Requirement Code	
		<i>Must use for other than PWR requirements to identify the type of war reserve requirement for which the forecast applies.</i>	
Must Use	LQ02	1271 Industry Code	X AN 1/30
		Code indicating a code from a specific industry code list	

Segment:	FST Forecast Schedule
Position:	410
Loop:	FST Optional (Must Use)
Level:	Detail
Usage:	Optional (Must Use)
Max Use:	1
Purpose:	To specify the forecasted dates and quantities
Syntax Notes:	<ol style="list-style-type: none"> 1 If either FST06 or FST07 is present, then the other is required. 2 If either FST08 or FST09 is present, then the other is required.
Semantic Notes:	<ol style="list-style-type: none"> 1 If FST03 equals "F" (indicating flexible interval), then FST04 and FST05 are required. FST04 would be used for the start date of the flexible interval and FST05 would be used for the end date of the flexible interval.
Comments:	<ol style="list-style-type: none"> 1 As qualified by FST02 and FST03, FST04 represents either a discrete forecast date, the first date of a forecasted bucket (weekly, monthly, quarterly, etc.) or the start date of a flexible interval. 2 FST06 qualifies the time in FST07. The purpose of the FST07 element is to express the specific time of day in a 24-hour clock to satisfy "just-in-time" requirements. As an alternative, the ship/delivery pattern segment (SDP) may be used to define an approximate time, such as a.m. or p.m.
Notes:	<ol style="list-style-type: none"> 1. Use multiple 2/FST/410 loop iterations to identify incremental monthly forecast quantities for other than PWR requirements associated with the War Reserve Material Requirements Code identified in the 2/LM/390 loop. 2. Use only two iterations of the 2/FST/410 loop when identifying the PWR requirement. One occurrence must include a FST02 code of D and the second must include a FST02 code of S.

Data Element Summary

	Ref.	Data	Attributes
	Des.	Element Name	
Must Use	FST01	380 Quantity	M R 1/15
		Numeric value of quantity	
		<i>Use to identify the monthly forecast quantity. Express as a whole number with no decimal.</i>	
Must Use	FST02	680 Forecast Qualifier	M ID 1/1
		Code specifying the sender's confidence level of the forecast data or an action associated with a forecast	
		D Planning	
		<i>Use for all Other War Reserve Material Requirements (OWMR), repairable return, and Pre-positioned War Reserve Material Requirements (PWRMR) (non-protected) transactions to indicate the requirement reflects a planning requirement forecast.</i>	
		S Strike Protection	

Use for all PWRMR (protected) transactions to indicate the requirement reflects a protected requirement forecast.

Must Use	FST03	681	Forecast Timing Qualifier	M ID 1/1
			Code specifying interval grouping of the forecast	
			M Monthly Bucket (Calendar Months)	
			<i>Use to indicate quantities are reflected in monthly increments.</i>	
Must Use	FST04	373	Date	M DT 8/8
			Date expressed as CCYYMMDD	
			<i>Use to identify the specific month of the forecast period for which the quantity applies. Assume that the first day of the month applies.</i>	
Not Used	FST05	373	Date	O DT 8/8
			Date expressed as CCYYMMDD	
Not Used	FST06	374	Date/Time Qualifier	X ID 3/3
			Code specifying type of date or time, or both date and time	
Not Used	FST07	337	Time	X TM 4/8
			Time expressed in 24-hour clock time as follows: HHMM, or HHMMSS, or HHMMSSD, or HHMMSSDD, where H = hours (00-23), M = minutes (00-59), S = integer seconds (00-59) and DD = decimal seconds; decimal seconds are expressed as follows: D = tenths (0-9) and DD = hundredths (00-99)	
Not Used	FST08	128	Reference Identification Qualifier	X ID 2/3
			Code qualifying the Reference Identification	
Not Used	FST09	127	Reference Identification	X AN 1/30
			Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier	
Not Used	FST10	783	Planning Schedule Type Code	O ID 2/2
			Code identifying type of planning schedule used	

Segment:	SDQ Destination Quantity
Position:	420
Loop:	FST Optional (Must Use)
Level:	Detail
Usage:	Optional
Max Use:	50
Purpose:	To specify destination and quantity detail
Syntax Notes:	<ol style="list-style-type: none"> 1 If either SDQ05 or SDQ06 is present, then the other is required. 2 If either SDQ07 or SDQ08 is present, then the other is required. 3 If either SDQ09 or SDQ10 is present, then the other is required. 4 If either SDQ11 or SDQ12 is present, then the other is required. 5 If either SDQ13 or SDQ14 is present, then the other is required. 6 If either SDQ15 or SDQ16 is present, then the other is required. 7 If either SDQ17 or SDQ18 is present, then the other is required. 8 If either SDQ19 or SDQ20 is present, then the other is required. 9 If either SDQ21 or SDQ22 is present, then the other is required.
Semantic Notes:	1 SDQ23 identifies the area within the location identified in SDQ03, SDQ05, SDQ07, SDQ09, SDQ11, SDQ13, SDQ15, SDQ17, SDQ19, and SDQ21.
Comments:	<ol style="list-style-type: none"> 1 SDQ02 is used only if different than previously defined in the transaction set. 2 SDQ03 is the store number. 3 SDQ23 may be used to identify areas within a store, e.g., front room, back room, selling outpost, end aisle display, etc. The value is agreed to by trading partners or industry conventions.

Data Element Summary

	<u>Ref.</u> <u>Des.</u>	<u>Data</u> <u>Element</u>	<u>Name</u>	<u>Attributes</u>
Must Use	SDQ01	355	Unit or Basis for Measurement Code Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken <i>DLMS users see the Unit of Issue and Purchase Unit Conversion Table for applicable codes.</i> Refer to 004010 Data Element Dictionary for acceptable code values.	M ID 2/2
Not Used	SDQ02	66	Identification Code Qualifier Code designating the system/method of code structure used for Identification Code (67)	O ID 1/2
Must Use	SDQ03	67	Identification Code Code identifying a party or other code <i>Use any acceptable value to satisfy X12 mandatory syntax rules.</i>	M AN 2/80
Must Use	SDQ04	380	Quantity Numeric value of quantity <i>Use any acceptable value to satisfy X12 mandatory syntax rules.</i>	M R 1/15
Not Used	SDQ05	67	Identification Code Code identifying a party or other code	X AN 2/80

Not Used	SDQ06	380	Quantity Numeric value of quantity	X	R 1/15
Not Used	SDQ07	67	Identification Code Code identifying a party or other code	X	AN 2/80
Not Used	SDQ08	380	Quantity Numeric value of quantity	X	R 1/15
Not Used	SDQ09	67	Identification Code Code identifying a party or other code	X	AN 2/80
Not Used	SDQ10	380	Quantity Numeric value of quantity	X	R 1/15
Not Used	SDQ11	67	Identification Code Code identifying a party or other code	X	AN 2/80
Not Used	SDQ12	380	Quantity Numeric value of quantity	X	R 1/15
Not Used	SDQ13	67	Identification Code Code identifying a party or other code	X	AN 2/80
Not Used	SDQ14	380	Quantity Numeric value of quantity	X	R 1/15
Not Used	SDQ15	67	Identification Code Code identifying a party or other code	X	AN 2/80
Not Used	SDQ16	380	Quantity Numeric value of quantity	X	R 1/15
Not Used	SDQ17	67	Identification Code Code identifying a party or other code	X	AN 2/80
Not Used	SDQ18	380	Quantity Numeric value of quantity	X	R 1/15
Not Used	SDQ19	67	Identification Code Code identifying a party or other code	X	AN 2/80
Not Used	SDQ20	380	Quantity Numeric value of quantity	X	R 1/15
Not Used	SDQ21	67	Identification Code Code identifying a party or other code	X	AN 2/80
Not Used	SDQ22	380	Quantity Numeric value of quantity	X	R 1/15
Not Used	SDQ23	310	Location Identifier Code which identifies a specific location	O	AN 1/30

Segment:	LM Code Source Information
Position:	430
Loop:	LM Optional
Level:	Detail
Usage:	Optional
Max Use:	1
Purpose:	To transmit standard code list identification information
Syntax Notes:	
Semantic Notes:	
Comments:	1 LM02 identifies the applicable industry code list source information.
Notes:	<p><i>1. Use this 2/LM/430 loop to identify coded information maintained in departmental or agency documentation.</i></p> <p><i>2. Use this 2/LM/430 loop for OWMR and repairable return transactions to stratify monthly forecasts by project code.</i></p> <p><i>3. Use this 2/LM/430 loop for PWR transactions to stratify monthly forecasts by type of WRM and/or project code.</i></p>

Data Element Summary

	<u>Ref.</u>	<u>Data</u>	<u>Element</u>	<u>Name</u>	<u>Attributes</u>
Must Use	LM01	559	Agency Qualifier Code	Code identifying the agency assigning the code values DF Department of Defense (DoD)	M ID 2/2
Not Used	LM02	822	Source Subqualifier	A reference that indicates the table or text maintained by the Source Qualifier	O AN 1/15

Segment: **LQ** Industry Code
Position: 440
Loop: LM Optional
Level: Detail
Usage: Mandatory
Max Use: 100
Purpose: Code to transmit standard industry codes
Syntax Notes: 1 If LQ01 is present, then LQ02 is required.
Semantic Notes:
Comments:
Notes: *Use to identify codes, as appropriate, consistent with management information requirements.*

Data Element Summary

Ref.	Data			Attributes
<u>Des.</u>	<u>Element</u>	<u>Name</u>		
Must Use	LQ01	1270	Code List Qualifier Code	O ID 1/3
			Code identifying a specific industry code list	
		78	Project Code	
			Codes that relate a transaction to special programs, exercises, projects, operations, or other purposes	
			<i>Use as needed to identify the applicable war reserve project code.</i>	
		COG	Cognizance Symbol	
			<i>Use to identify the material cognizance symbol (COG) of the end item. Indicate NSL for non-stock numbered listed items. This is a Navy-unique data element meaningful to Navy only; Non-Navy Components are to perpetuate without action.</i>	
		IMC	Item Management Code	
			<i>Use to identify the Item Management Code (IMC) for integrated material management. Indicate NSL for non-stock numbered listed items. This is a Navy-unique data element meaningful to Navy only; Non-Navy Components are to perpetuate without action.</i>	
		LZ	War Reserve Material Requirement Code	
			<i>Must use to identify PWR requirement forecast.</i>	
		MCC	Material Control Code	
			<i>Use to identify the Material Control Code (MCC) for special inventory reporting. Indicate NSL for non-stock numbered listed items. This is a Navy-unique data element meaningful to Navy only;</i>	

Non-Navy Components are to perpetuate without action.

SMI

Special Material Identification Code

Use to identify the Special Material Identification Code (SMIC) for an end item. Indicate NSL for non-stock numbered listed items. This is a Navy -unique data element meaningful to Navy only; Non-Navy Components are to perpetuate without action.

Must Use

LQ02

1271

Industry Code

X AN 1/30

Code indicating a code from a specific industry code list

Segment: **SE** Transaction Set Trailer
Position: 020
Loop:
Level: Summary
Usage: Mandatory
Max Use: 1
Purpose: To indicate the end of the transaction set and provide the count of the transmitted segments (including the beginning (ST) and ending (SE) segments)

Syntax Notes:**Semantic Notes:**

Comments: 1 SE is the last segment of each transaction set.

Data Element Summary

	Ref.	Data		
	<u>Des.</u>	<u>Element</u>	<u>Name</u>	<u>Attributes</u>
Must Use	SE01	96	Number of Included Segments	M N0 1/10
			Total number of segments included in a transaction set including ST and SE segments	
Must Use	SE02	329	Transaction Set Control Number	M AN 4/9
			Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set	
			<i>Cite the same number as the one cited in ST02.</i>	